

Product datasheet

Specifications



Charging station, Schneider Charge Pro, 1P-3P, 1xAtt. cable, 7.4-11-22kW, 16-32A

EVB4S22NC0

Main

Range	Schneider Charge Pro
Product name	Schneider Charge Pro
Product or component type	Charging station
Poles description	1P or 3P
Mounting mode	Wall-mounted Pedestal mount
Mounting support	Pedestal, to be ordered separately
Type of installation	Indoor/outdoor
Nominal output power	7.4 kW 32 A 230 V 11 kW 16 A 400 V 22 kW 32 A 400 V
Output type	Charging cable T2 bottom 7 m
Access control system	Free access Badge MIFARE DESFire EV1 Badge MIFARE DESFire EV2 Badge MIFARE RFID authentication card MIFARE DESFire EV1 RFID authentication card MIFARE DESFire EV2 RFID authentication card MIFARE
Quantity per set	Set of 1

Complementary

Provided equipment	1 residual direct current detection device (RDC-DD) integrated 1 Wi-Fi module integrated 2 Ethernet interface module integrated
Protection device type	Residual direct current detection device (RDC-DD) - 6 mA
[Us] rated supply voltage	220...240 V AC 50/60 Hz +/- 10 % 380...415 V AC 50/60 Hz +/- 10 %
Earthing system	TT TN-S TN-C IT only between 220 VAC and 240 VAC
Number of inputs	1
Input type	Auxiliary for dynamic energy management NO contact Auxiliary for dynamic energy management NC contact Anti-tripping module for dynamic energy management Auxiliary contact for external iMNX
Control type	1 white push-button

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	On charge: LED (blue) Error: LED (red) Available: LED (green) Start: LED (white) Reserved: LED (orange)
Height	418 mm
Width	292 mm
Depth	119 mm
Net weight	7 kg
Colour	Black (RAL 9005)
Standards	EN/IEC 61851-1:2019 EN 61000-6-3:2007+A1:2011+AC:2012 EN 61000-6-2:2005+AC:2005 EN 61000-6-1:2007 EN/IEC 61000-6-1:2019 EN 61000-6-4:2007+A1:2011 ETSI EN 301 489-1:V1.9.2 (2011-09) EN/IEC 61000-6-3:2021 ETSI EN 301 489-1:V2.2.3 (2019-11) ETSI EN 301 489-3:V2.3.2 (2023-01) EN/IEC 61000-6-2:2019 ETSI EN 301 489-17:V3.2.4 (2020-09) ETSI EN 300 330:V2.1.1 (2017-02) ETSI EN 300 328:V2.2.2 (2019-07) EN/IEC 61000-6-4:2019 EN/IEC 63000:2018:2019 EN/IEC 61851-21-2:2021 EN/IEC 62311:2020 EN 18031-1:2024 EN 18031-2:2024 IEC 62955:2018 EN ISO 15118-1:2019 EN ISO 15118-2:2016 EN ISO 15118-3:2016 EN ISO 15118-4:2019 EN ISO 15118-5:2019 IEC 62196-1:2022 IEC 62196-2:2022
ISO 15118 module	To be ordered separately
Product certifications	CE UKCA EV Ready 2.0A
Maximum supply current	32 A
Communication network type	Wi-Fi Ethernet TCP/IP
Communication port protocol	OCPP 1.6J, for connection to CPO & CSMS OCPP 1.6J, for connection to EVCE Modbus RTU, for connection to external power meter Modbus TCP, for connection to external energy management system
Communication service	JSON smart charging
MID energy meter	Without
4G modem	Without

Environment

IP degree of protection	IP55
IK degree of protection	IK10
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-30...50 °C
Relative humidity	5...95 %

Operating altitude	0...2000 m
--------------------	------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	39.500 cm
Package 1 Length	58.000 cm
Package 1 Weight	9.930 kg
Unit Type of Package 2	P12
Number of Units in Package 2	12
Package 2 Height	102.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	131.000 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	0.3 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture	
Recyclability potential, in %	0
Removable battery	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins